

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by S.W. Lackland under General Land Office Contract No. 415. Surveyor General's notes state: Set basalt stone 16 x 12 x 5 in. 10 ins. in ground. For 1/4 sec corner marked 1/4 on W-Face. Raised mound of stone 2 ft. high 4 ft. base alongside.

DIAGRAM

T12S	R30E
S33	S34
1983	
PLS	848

Description of corner evidence found:

Found stone 16 x 10 x 6, 1/4 marked on W-Face set in ground, mound alongside.
Found two Bearing Trees which appear to be unrecorded originals accepted stone as 1/4 corner.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set a 30" x 2" aluminum pipe with 3 1/2" aluminum cap stamped as shown in diagram. Set monument 20" in ground with original stone North alongside. Set ring of stone around monument.
From which:
A Pine 15" dia. bears N32°W, 18.1 ft. scribed 1/4 S33 BT.
A Juniper 8" dia. bears N63°E, 13.1 ft. scribed 1/4 S34 BT.
Nailed brass washers tamped PLS 848, Bearing Tree & warning signs to each tree.
Painted 6" red band around each tree.
Set steel post with warning sign 5 ft. North.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Douglas M. Ferguson
**OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848**

Date May 13, 1983

Witnessed by Dan Martin

Office of.....Surveyor..... County of..... Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 29th day of August, 1983.
Douglas M. Ferguson by
(COUNTY OFFICIAL) (DEPUTY)