

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1869, by J.B. David, Under General Land Office Contract No. 131, Surveyor Generals Notes State:
Set stone 16x8x6, for corner to sections 36,31,1, & 6.

DIAGRAM

T12S
R29E R30E
S36 | S31
S1 | S6
T13S
1982
PLS848

Description of corner evidence found:

Found a 16x8x6 in. stone with 6 grooves on one face & 6 notches on opposite edge, lying loose in circle of stone. Accepted center of circle as Twp. corner.

11

Description of monument and accessories | established to perpetuate the original location of this corner:

Set a 30x2" aluminum pipe with 3x aluminum cap, stamped as shown in diagram.
Set 8" in the ground, & raised a mound of stone around pipe.
Placed original stone N/W alongside pipe, at top of mound.

From Which:

A Juniper 6" dia. bears N28°W, 44.5 ft. scribed T12S R29E S36 BT.
A Juniper " " " N61°E, 12.3 ft. scribed T12S R30E S31 BT.
A Juniper " " " S23°E, 33.2 ft. scribed T13S R30E S6 BT.
A Juniper " " " S55°W, 43.9 ft. scribed T13S R29E S1 BT.

Nailed brass washers stamped PLS848, bearing tree & warning signs to each tree.
Painted 6" red band around each tree.

Set steel posts with warning signs 7 ft. North.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 10-28-82

Witnessed by D. Mitchell Ferguson

Office of.....Surveyor..... County of.....Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the.....29th..... day of.....August....., 19.....83.
Robert D. Beyer by
(COUNTY OFFICIAL) (DEPUTY)