

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

U.S.F.S. INDEX No. Z-5 (Ammended)

History of original corner establishment:

Corner originally established in 1869 by J.B. David under G.L.O. contract No. 131. The Surveyor Generals notes state:
Set Stone 18x7x6 for corners to sections 31 & 32

This corner was then postitioned by proportionate measure as shown on M.O.S. 785.

This position was then Ammended on M.O.S. 1525

DIAGRAM

AM
T12S R30E
S31 | S32

S6 | S5
T13S
1983
PLS 848

Description of Corner Evidence Found:

Found the aluminum monument as set during M.O.S. 785 to be S 4°13'21"E, 26.94 ft. from the actual proportionate position See the Narrative on M.O.S. 1525) from which I find the following Accessories:

A Juniper 10" in dia. bears N73°45'W, 17.9 ft., scribed T12S R30E S31 BT

A Juniper 10" in dia. bears N78°08'E, 33.5 ft., scribed T12S R30E S32 BT

A Juniper 7" in dia. bears S49°30'E, 35.5 ft., scribed T13S R30E S5 BT

A Juniper 12" in dia. bears S27°20'W, 28.3 ft., scribed T13S R30E S6 BT

Description of monument and accessories I established to perpetuate the original location of this corner:

Stamped "AM" on the original aluminum cap as shown in the DIAGRAM
No new accessories established.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1989
DOUGLAS M. FERGUSON
848

This work was performed by:
Douglas M. Ferguson, PLS 848
Witnessed by:
Kenneth H. Delano Jr.
D. Mitchell Ferguson

Date: 9-3-99

Office of Surveyor County of GRANT
State of OR I hereby certify that the within instrument was
filed in this office for record on the 22 day of OCT, 19 99

Robert D. Bazett
(COUNTY OFFICIAL)

by _____
(DEPUTY)

Refer to Grant County Map No. 1525