

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. B-7

History of original corner establishment:
Grant County Survey Records show no
previous establishment of this Cor.

DIAGRAM

T12S R31E
C
N1/161S5
C
1986
PLS 848

Description of corner evidence found:
Grant County Survey Records show no
previous establishment of this Cor.

Description of monument and accessories I established to perpetuate the
original location of this corner:
Set 2-1/2" x 30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown,
on the **DIAGRAM**, SET 20" in the ground.
From Which.
A Pine 12" dia., Bears S86°E., 36.4 ft., scribed: C-N 1/16 S5 BT
A Pine 12" dia., Bears N68°W., 36.4 ft., scribed: C-N 1/16 S5 BT
(Note: Bearing and distance above are correct, 86-68, 36.4-36.4)
Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.
Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence posts with
warning & Boundary Signs, North & East 5 ft., from the corner.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

**OREGON
JULY 12, 1988
DOUGLAS M. FERGUSON
848**

This work is performed by:

Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.

On: June 26, 1986

Refer to Map of Survey No. 941

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*..... I hereby certify that the within instrument was filed in this office
for record on the.....*30*..... day of.....*Sept*..... 19.....*86*
.....*Robert A. Dept*..... by.....
(COUNTY OFFICIAL) (DEPUTY)