

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. B-9

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM


T12S R31E
N1/16
S5/54
1986
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 26" in the ground.
From Which.
A Fir 8" dia., Bears S82°W., 6.6 ft., scribed: N1/16 S5 BT
A Fir 8" dia., Bears S20°E., 8.2 ft., scribed: N1/16 S4 BT
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, East 5 ft., and West 4 ft., from the corner.



OREGON
JULY 12, 1908
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: June 26, 1986
Refer to Map of Survey No. 941

Office of... *Surveyor* ... County of... *Grant* ...
State of... *Oregon* ... I hereby certify that the within instrument was filed in this office
for record on the... *30* day of... *Sept* ... 19... *86* ...
... by ...
(COUNTY OFFICIAL) (DEPUTY)