

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. C-8

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T12S R31E
E1/16
C--C
S5
1986
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 15" in the toe of road fill and raised a mound of stone & earth around the pipe.

From Which:

A Pine 10" dia., Bears S50°20'W., 11.0 ft., scribed: C-E 1/16 S5 BT

A Juniper 6" dia., Bears N81°34'W., 45.8 ft., scribed: C-E 1/16 S5 BT

Measurements to trees taken with an electronic tacheometer, with angles turned from the survey control network.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, South 8 ft., & West 12 ft. from the corner.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

OREGON
JULY 12, 1969
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: July 3, 1986
Refer to Map of Survey No. 941

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*..... I hereby certify that the within instrument was filed in this office
for record on the.....*30*..... day of.....*Sept*....., 19.....*86*
.....*Robert D. Baggett*..... by.....
(COUNTY OFFICIAL) (DEPUTY)