

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. D-7

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T12S R31E
C
S1/16185
C
1986
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 24" in the ground.

From Which:

A Pine 9" dia., Bears S65°W., 17.6 ft., scribed: C-S 1/16 SS BT

A Pine 8" dia., Bears S54°E., 22.9 ft., scribed: C-S 1/16 SS BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, South & West 5 ft. from the corner.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

OREGON
JULY 12, 1969
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: July 3, 1986
Refer to Map of Survey No. 941

Office of Sumner County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 30 day of Sept, 1986
Rolund D. Begett by _____
(COUNTY OFFICIAL) (DEPUTY)