

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. G-9

History of original corner establishment:

Corner is originally established by
Herman D. Graddon, Sept., 1881, under
General Land Office" Contract No. 416.
Surveyor Generals Notes State:
Set a basalt stone 16x12x4 ins. 10 ins
in the ground, for 1/4 sec. cor. marked,
1/4 on W. face and raised a stone
mound alongside.

DIAGRAM

T12S R31E
1/4
S81S9
1986
PLS 848

Description of corner evidence found:

Found 18"x12"x5" stone with 1/4 on West face, set
in a mound of stone, The corner looks like it has
never been found or disturbed since it was originally
set.
There are no accessories originally established.
Accepted the above described stone as the 1/4 Cor.

Description of monument and accessories I established to perpetuate the
original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET on solid rock, set the original stone North
alongside pipe and raised a mound of stone around the pipe.
From Which:
A Pine 21" dia., Bears N30°E., 18.2 ft., scribed: 1/4 S9 BT
A Juniper 6" dia., Bears N44°W., 95.3 ft., scribed: 1/4 S8 bt
Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.
Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence post with
warning Sign, South alongside pipe in the stone mound.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1986
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.

On: July 11, 1986

Refer to Map of Survey No. 941

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 11th day of Sept, 1986
Robert H. Sargent by Douglas M. Ferguson
(COUNTY OFFICIAL) (DEPUTY)