


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by John B. David under GLO contract number 131 dated June 8, 1869. Surveyor General record states:

Set stone 18x12x7 for corner to Secs. 23,24,25 & 26



No record of subsequent remonumentation was found in the Grant County records

Description of corner evidence found:

Found stone 18x12x7 marked with 1 and 2 notches

See map of survey dated January, 1985

Description of monument and accessories I established to perpetuate the original location of this corner: In place of stone I set a 2½ inch x 30 inch aluminum pipe with aluminum cap marked as shown 30 inches in the ground, from which:

New BTs

- A 8 inch diameter P.Pine bears N31°E 15.2 feet marked T12S R31E S24 BT
- A 15 inch diameter P.Pine bears S66°E 36.1 feet marked T12S R31E S25 BT
- A 11 inch diameter P.Pine bears S87°W 28.3 feet marked T12S R31E S26 BT
- A 15 inch diameter Red Fir bears N38°W 53.5 feet marked T12S R31E S23 BT


Buried the original stone East and alongside of monument

Raised small mound of stone around monument

Set steel fenceposts approximately 5 feet East with 54-2 sign and approximately 5 feet North with 54-2 and 54-4 sign

Corner set August 21, 1984

Witness: Mike Wagner



**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

OREGON
JULY 10, 1984
DUANE I. GRIFFITH
644

I used a steel tape and magnetic compass in the establishment of these accessories. I used 20° East magnetic declination and the distance to the BTs are to the center of the tree. I set a brass washer marked OPLS 644 at the BT blaze. I painted a 6 inch red band around all BTs and attached 54-3 and 54-4 signs.

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*..... I hereby certify that the within instrument was filed in this office
for record on the.....*14 Feb*..... day of.....*1985*.....
.....*Robert D. Baggett*..... by.....
(COUNTY OFFICIAL) (DEPUTY)