

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1869, by J.B. David, Under General Land Office Contract No. 131, Surveyor Generals Notes State:
Set a basalt stone 18x7x5 for corner sections 32,33,4,&5.

DIAGRAM

T12S R31E
S32 | S33
S5 | S4
T13S
1982
PLS848

Description of corner evidence found:

Found a 19x9x5 in. stone with 4 grooves on East side, set in large mound of stone.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3½" aluminum cap, stamped as shown in diagram.
Set 18" in the ground, & raised a mound of stone around pipe.
From Which:

Set steel posts with warning & bearing tree signs.
Bear North 5.7 ft. East, 4.9 ft. South, 5.5 ft. and West 6.1 ft. from corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 11-9-82
Witnessed by D. Mitchell Ferguson

Office of.....Surveyor..... County of.....Grant
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 29th day of August 1983.
Robert D. Baggett by
(COUNTY OFFICIAL) (DEPUTY)