

History of original corner establishment:

Corner established in 1881 by Robb and Gradon under General Land Office Contract No. 383.

Surveyor General Record states;

Set post for corner to sections 1,2,11 and 12 from which;

A fir 8" diameter bears N 45° E, 77 links dist.

A fir 7" diameter bears N 35° W, 23 links dist.


A fir 8" diameter bears S 5° W, 67 links dist.

A fir 7" diameter bears S 82° E, 65 links dist.

DIAGRAM

T12S

R32E



No record of subsequent remonumentation was found in county records.
Description of corner evidence found:

Found mound of stone and 3 BTs

See map of survey dated September, 1980.
Description of monument and accessories established to perpetuate the original location of this corner:

At call distances from BTs I set 2 1/2' x 30" aluminum monument marked as shown 28" in ground from which;

ORIGINAL BTs

A 18" fir bears N 45° E, 50.8 ft, scribes visible

A 15" fir bears S 83° E, 42.9 ft scribes visible, dead and down

A 16" fir bears N 36° W, 15.2 ft, scribes visible, live vigorous

NEW BTs

A 12" fir bears N 9° E, 51.8 ft marked T12S R32E S1 BT

A 9" fir bears S 78° E, 68.6 ft marked T12S R32E S12 BT


A 14" tamarack bears S 34° W, 29.9 ft marked T12S R32E S11 BT

Raised mound of stone

T12S R32E

S2	S1
S11	S12

1980
OPLS 644



Duane I. Griffith

OREGON
JULY 10, 1964
DUANE I. GRIFFITH
644

Brass washer nailed to BT blaze.
Used steel tape and magnetic compass
with 15° East declination.
Measured to center of new B.T.s

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*31*..... day of.....*Oct*....., 19.....*80*
.....*Robert D. Beyer*..... by.....
(COUNTY OFFICIAL) (DEPUTY)