

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by John B. David under GLO contract number 131, dated June 8, 1869.

Surveyor General record states:

Set stone 14x9x6 for corner to Secs 18,19,13 & 24

DIAGRAM

T12S	
R31E	R32E
S 13	S 18
S 24	S 19

Description of corner evidence found:

NONE

The area is on a rather steep rocky sidehill. I find evidence of considerable wash over the years. I feel it is very possible the stone has been washed away.

Description of monument and accessories I established to perpetuate the

original location of this corner: At proportionate position, I set a 2½" x 30" aluminum pipe with aluminum cap marked as shown, 14 inches in the ground, from which:

New BTs

A 8 inch diameter Juniper bears North 43° East, 99.7 feet, marked T12S R32E S18 BT
A 12 inch diameter P.Pine bears South 15° East, 73.3 feet, marked T12S R32E S19 BT
A 8 inch diameter Juniper bears South 14° West, 56.3 feet, marked T12S R31E S24 BT
A 12 inch diameter Juniper bears North 68° West, 22.3 feet, marked T12S R31E S13 BT

Raised mound of stone around new monument

Attached 54-4 sign and bearing tree tags to and painted a 6 inch red band around all bearing trees

Set a steel fence post approximately 5 feet West with 54-4 sign attached


Corner set October 20, 1983

Witnesses: Robert Bagett, Greg Blackman

See survey number 792

T12S	
R31E	R32E
S 13	S 18
S 24	S 19

1983
OPLS 644



I used a steel tape and magnetic compass in the establishment of these accessories. I used 17½° East magnetic declination, and the distances to the new BTs are to the center of the tree. I attached a brass washer marked OPLS 644 by the BT blaze of the new BTs.

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 30 day of Nov, 1983
Robert D. Bagett by _____
(COUNTY OFFICIAL) (DEPUTY)