

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by John B. David under GLO contract number 131, dated June 8, 1869.

Surveyor General record states:

Set stone 14x9x6 for corner to Secs 17, 18, 19 & 20

DIAGRAM

T12S R32E

S 18 | S 17

S 19 | S 20

Description of corner evidence found:

Found marked stone, called size, loose on ground

Description of monument and accessories I established to perpetuate the

original location of this corner: In place of stone, I set a 2½" x 30" aluminum pipe with aluminum cap marked as shown, 26 inches in the ground, from which:

New BTs

- A 9 inch diameter White Fir bears North 57° East, 15.2 feet, marked T12S R32E S17 BT
- A 18 inch diameter tamarack bears South 72° East, 15.4 feet marked T12S R32E S20 BT
- A 11 inch diameter White Fir bears South 84° West, 14.9 feet, marked T12S R32E S19 BT
- A 12 inch diameter tamarack bears North 51° West, 11.5 feet, marked T12S R32E S18 BT

Buried the original stone North and alongside of the new monument

Raised mound of stone around new monument

Attached 54-4 signs and bearing tree tags to and painted a 6 inch red band around all bearing trees

Set steel fence post approximately 5 feet South with 54-4 sign

Corner set October 13, 1983

Witnesses: Greg Blackman and Rick Robinson

See survey number 792

T12S R32E

S 18 | S 17

S 19 | S 20

1983

OPLS 644

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 10, 1954
DUANE I. GRIFFITH
644

I used a steel tape and magnetic compass in the establishment of these accessories. I used 17½° East magnetic declination, and the distances to the new BTs are to the center of the tree. I attached a brass washer marked OPLS 644 by the BT blaze of the new bearing trees.

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 20 day of NOV, 1983
Robert D. Bayett by _____
(COUNTY OFFICIAL) (DEPUTY)