

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. A-14

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T11S R33E
S34
W1/16-.-
S3
T12S
1986
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 14" in the ground and raised a mound of stone & earth around the pipe.

From Which.

A Pine 7" dia., Bears N 9°W., 54.3 ft., scribed: W1/16 S34 BT

A Pine 7" dia., Bears S71°E., 15.1 ft., scribed: W1/16 S3 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence post with warning Sign, North 6 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1988
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: July 15, 1986
Refer to Map of Survey No. 949

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*..... I hereby certify that the within instrument was filed in this office
for record on the.....*24*..... day of.....*Oct*....., 19.....*86*.....
.....*Robert D. Bright*..... by.....
(COUNTY OFFICIAL) (DEPUTY)