

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. C-9

History of original corner establishment:

Corner was originally established by
Robb & Graddon, in 1891, under joint
General Land Office Contract No. 383.
The U.S. Surveyor Generals Notes State:
Set stone 17x12x5 for 1/4 Sec. Cor.

DIAGRAM

T12S R33E
1/4
S51S4
1988
PLS 848

from which

A Pine 26 in. dia. bears N40°W., 15 lks. dist.
" Fir 28 " " " S12°E., 70 " "

Description of corner evidence found:

Found a stone, 17"x12"x5", set vertical in ground
with 1/4 on the East face.

From Which:

A Pine 40" dia., Bears N53°W., 13.0 ft, to
center of the tree. Said pine has a blaze with BT
visible. (Record N40°W., 9.9 ft.
Accepted the above described stone as the 1/4 Sec. Cor


**Description of monument and accessories | established to perpetuate the
original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET 27" in the ground.

From Which:

(New Bearing Trees)

A Fir 8" dia., Bears S12°W., 25.3 ft., scribed: 1/4 S5 BT
Tamarack 8" dia., Bears S38°E., 28.2 ft., scribed: 1/4 S4 BT
Measurements to trees taken with metal tape and magnetic compass with
20° East declination set off.
Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence posts with
warning & Boundary Signs, South & East 3 ft. from the corner.



This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: June 28, 1988

Refer to Map of Survey No. 1068
Witnesses: D. Mitchell Ferguson & Ken Delano

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 25 day of July, 1987
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)