

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. C-10

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

In 1959, Howard Taylor placed a mound of stone at the approx. 1/16 corner position and tagged a 5" Fir, South 3.5 ft. from such.

DIAGRAM

T12S R33E
W1/16
C.-C
S 4
1988
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this corner.
Found a small mound of stone NE 6 ft. from this corner.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 23" in the ground and raised a mound of stone around the pipe.

From Which:

A Fir 10" dia., Bears S34⁰E., 29.0 ft., scribed: CW1/16 S4 BT

A fir 10" dia., Bears West., 33.7 ft., scribed: CW1/16 S4 BT

Measurements to trees taken with metal tape and magnetic compass with 20⁰ East declination set off.

Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, North & West 3 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1960
DOUGLAS M. FERGUSON
848

This work is performed by:

Douglas M. Ferguson PLS 848

Mt. Vernon Oregon.

On: June 28, 1988

Refer to Map of Survey No. 1068

Witnesses: D. Mitchell Ferguson & Ken Delano

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 25 day of July, 1989
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)