

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. D-12

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor. In 1959, Howard Taylor placed a mound of stone at the approx. 1/16 corner position and tagged a 3" Pine S42°E., 3.5 ft from such mound.

DIAGRAM

T12S R33E
SE1/16
S4
1988
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this corner. Found a small mound of stone SE 13 ft. from this corner.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 28" in the ground.

From Which:

A Fir 14" dia., Bears S19°W., 13.2 ft., scribed: SE1/16 S4 BT

A Fir 10" dia., Bears N80°W., 14.8 ft., scribed: SE1/16 S4 BT

Measurements to trees taken with metal tape and magnetic compass with 20° East declination set off.

Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, North 1.5 & West 2 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1953
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.

On: June 22, 1988

Refer to Map of Survey No. 1068

Witnesses: D. Mitchell Ferguson & Ken Delano

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 25 day of July, 1987
Robert D. Delano by _____
(COUNTY OFFICIAL) (DEPUTY)