

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No G-7

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T12S R33E
C1/4
S8
1988
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 26" in the ground.

From Which:

A Juniper 12" dia., Bears N68°W., 46.6 ft., scribed: C1/4 S8 BT

A Pine 24" dia., Bears N26°E., 24.5 ft., scribed: C1/4 S8 BT

Measurements to trees taken with metal tape and magnetic compass with 20° East declination set off.

Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, East 2 ft. and West 40 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1983
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.

On: July 6, 1988

Refer to Map of Survey No. 1068

Witnesses: D. Mitchell Ferguson & Ken Delano

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 25 day of July, 1988
Douglas M. Ferguson by _____
(COUNTY OFFICIAL) (DEPUTY)