


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

A. Corner not set by GLO



Description of corner evidence found:
B. Not set by GLO

Description of monument and accessories I established to perpetuate the original location of this corner:

SET MON. 23 JULY 1989

C. I set a 2.5 inch dia. by 30 inch aluminum monument 24 inches in the ground. No stones available. I mark the cap:

T12S R34E WM
 C 1/4
 +

S10
 1989

STRYKER PLS 2060

NEW ACCESSORIES ESTABLISHED

13" douglas fir bears S87E at 31.2 ft scribed "C 1/4 S10 BT"
 24" ponderosa pine bears N84W at 12.8 ft scribed "C 1/4 S10 BT"

Painted red band around each bearing tree
 placed brass washer with "PLS 2060" at base of each new BT blaze
 placed USDA Forest Service metal signs 54-3 (BT) and 54-9 (LSM) on each bearing tree. placed a 54-4 (ATTENTION) sign on tree near corner.
 This corner established as part of GRANT COUNTY SURVEY MAP NO. 1103

Office of..... Sumner County of..... Grant
 State of..... Ore gon I hereby certify that the within instrument was filed in this office
 for record on the..... 1 day of..... Dec 19..... 89
Edwin A. Stryker by
 (COUNTY OFFICIAL) (DEPUTY)

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

Edwin A. Stryker

OREGON
 JULY 15, 1983
 EDWIN A. STRYKER
 2060