CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
NONE

T. 12S. R. 26 E.

CORNERSTONE SURVEYING INC
S1/16
S27 | S26
1997
OPLS 2734

Description of corner evidence found:
NONE

REGISTERED
PROFESSIONAL
LAND SURVEYOR
OREGON
SEPTEMBER 19, 1995
JACK L. WATSON
2734
RENEWAL DATE: 6/30/98

See Record Map of Survey No. 1443.

Description of monument and accessories set at corner location:
At the corner position determined by survey I set a 5/8" x 30" iron pin with attached 2" aluminum cap, driven 24 inches in the ground. The cap is stamped as shown in the diagram.

From which I set reference monuments:
A 5/8"x30" iron pin bears S67°E, 28.79 feet, with attached red plastic cap marked CORNERSTONE SURVEYING, Inc.
A 5/8"x30" iron pin bears S57°W, 21.80 feet, with attached red plastic cap marked CORNERSTONE SURVEYING, Inc.

I used a steel tape and magnetic compass, with 20° E. declination, to tie references.

Date: June 9, 1997

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 23 day of July, 1997.
Robert D. Bagott by .....
(COUNTY OFFICIAL) (DEPUTY)

U-17