CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
NONE

T. 12 S., R. 26 E.

CORNERSTONE SURVEYING INC
SW1/16 S26
1997
OPLS 2734

Description of corner evidence found:
NONE

REGISTERED
PROFESSIONAL
LAND SURVEYOR
OREGON
SEPTEMBER 19, 1995
JACK L. WATSON
2734
RENEWAL DATE: 6/30/98

See Record Map of Survey No. 1443.

Description of monument and accessories set at corner location:
At the corner position determined by survey I set a 5/8" x 30" iron pin with attached 2" aluminum cap, driven 28 inches in the ground, surrounded by a mound of stone. The cap is stamped as shown in the diagram.

From which I set new reference point:
A 5/8"x30" iron pin bears S6°E, 24.67 feet, with attached red plastic cap marked CORNERSTONE SURVEYING, INC.

From which I scribe a new bearing tree:
A 12" Juniper bears N75°W, 38.77 feet, marked SW1/16S26BT.

I used a steel tape measuring to a 50d nail driven in the side center at the root crown of the BT and magnetic compass, with 20° E. declination.

Date: June 9, 1997

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 23 day of July, 1997.
Robert D. Sargent by .....
(COUNTY OFFICIAL) (DEPUTY)