CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
NONE

T. 12 S. R. 26 E.

CORNERSTONE SURVEYING INC
NE1/16 S35
1997
OPLS 2734

Description of corner evidence found:
NONE

REGISTERED
PROFESSIONAL
LAND SURVEYOR
OREGON
SEPTEMBER 19, 1995
JACK L. WATSON
2734
RENEWAL DATE: 6/30/98

See Record Map of Survey No. 1443.

Description of monument and accessories set at corner location:
At the corner position determined by survey I set a 5/8" x 30" iron pin with attached 2" aluminum cap, driven 26 inches in the ground, surrounded by a mound of stone. The cap is stamped as shown in the diagram.

From which I scribe new bearing trees:
A 5" Juniper bears East, 18.39 feet, marked XBT.
A 10" Juniper bears S63°W, 64.18 feet, marked NE1/16S35BT.

I used a steel tape measuring to a 50d nail driven in the side center at the root crown of the BT's and magnetic compass, with 20° E. declination.

Date: June 9, 1997

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 23 day of July, 1997.
Robert D. Boyett by .....
(COUNTY OFFICIAL) (DEPUTY)