CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. A-3

History of original corner establishment:

Corner is originally established by
Robb & Gradon, in 1881, under "General
Land Office" Contract No. 383.
Surveyor Generals Notes State:
Set Stone 16x14x3 in stone mound
for 1/4 Sec. Cor.

DIAGRAM

T11S R33E
S31
1/4-.-
S6
T12S
1986
PLS 848

Description of corner evidence found:

Found 15x13"x3" stone, set in a mound of stone,
with "1/4" marked on North face.
Martin Louther found this corner and described the
stone, in his unrecorded notes of 1959.
No accessories are originally established.
Accepted the above described stone as the 1/4 Sec.Cor.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 26" in the ground, Set the original stone North alongside and placed a ring of stone filled with earth around the pipe.
From Which:
A Fir 6" dia., Bears North, 19.7 ft., scribed:1/4 S31 BT
A Fir 6" dia., Bears S 8°E., 1.5 ft., scribed:1/4 S6 BT
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, East 3 ft. & West 5 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt.Vernon Oregon.
On: July 30,1986
Refer to Map of Survey No. 949

Office of Surveyor *County of* Grant
State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 24 *day of* Oct, 19 86
Robert D Bagett *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆U.S. GOVERNMENT PRINTING OFFICE-1983-793-276

A-3