CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No B-9

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor. In 1959, Howard Taylor placed a mound of stone at the approx. 1/16 corner position and tagged a 14" Tamarack, S42°W., 7 ft. from such.

DIAGRAM

T12S R33E
N 1/16
S5|S4
1988
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this corner.
Found a small mound of stone NW 2 ft. from this corner.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 20" in the ground and raised a mound of stone & earth around the pipe.
From Which:
Tamarack 16" dia., Bears N60°E., 9.2 ft., scribed: N1/16 S4 BT
Tamarack 14" dia., Bears N49°W., 62.4 ft., scribed: N1/16 S5 BT
Measurements to trees taken with metal tape and magnetic compass with 20° East declination set off.
Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, North 6 ft. & East 3 ft. from the corner.

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 12, 1988
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt.Vernon Oregon.
On: June 30, 1988
Refer to Map of Survey No. 1068
Witnesses: D.Mitchell Ferguson & Ken Delano

Office of Surveyor *County of* Grant
State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 25 *day of* July, *19* 89
Stanley Bryant *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

B-9