CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. B-16

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T12S R33E
NE1/16
S3
1986
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 24" in the ground.
From Which.
A Pine 12" dia., Bears S74°E., 17.2 ft., scribed: NE 1/16 S3 BT
A Fir 7" dia., Bears S62°W., 10.1 ft., scribed: NE 1/16 S3 BT
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, North and East approx. 5 ft. from the corner.

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt.Vernon Oregon.
On: July 15,1986
Refer to Map of Survey No. 949

Office of Surveyor *County of* Grant
State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 24 *day of* Oct *, 19*86
Robert D Bagett *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆U.S. GOVERNMENT PRINTING OFFICE - 1983-793-276

B-16