CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No G-15

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

In 1959, Howard Taylor placed a mound of stone at the approx. 1/16 corner

DIAGRAM

T12S R33E
C1/4
S10
1988
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this corner.
Found a small mound of stone NE 5 ft. from this corner.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 25" in the ground.
From Which:
A Fir 12" dia., Bears S25°E., 38.4 ft., scribed: C1/4 S10 BT
A Pine 12" dia., Bears N70°W., 35.2 ft., scribed: C1/4 S10 BT
Measurements to trees taken with metal tape and magnetic compass with 20° East declination set off.
Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, South 4 ft. & West 3 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 18, 1989
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt.Vernon Oregon.
On: June 29, 1988
Refer to Map of Survey No. 1068
Witnesses: D.Mitchell Ferguson & Ken Delano

Office of...Surveyor..... *County of*...Grant.....
State of...Oregon....., *I hereby certify that the within instrument was filed in this office for record on the*...25... *day of*...July..... , 19..89...
...Robert D. Bayer..... *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

G-15