


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Levi C. Walker under General Land Office Contract No. 374 dated Sept. 27, 1880.

Surveyor Generals records state:

N 89°56' W on true line south boundary of section 35 80.00 Set for corner to sections 34, 35, 2 & 3 a basalt stone 16X12X8 in stone mound



Z-17

Description of corner evidence found:

Found a basalt stone 15"X12"X7" on top of stone mound consisting of 12 smaller stones, mound approx. 2 1/2 foot diameter. Stone appears marked with 2 notches on east side of stone.

Description of monument and accessories | established to perpetuate the original location of this corner:

As the evidence in the corner vicinity agrees with the G.L.O. original record, at the location of the found original stone in mound of stones, set 30 inch long 2 inch I.D. aluminum pipe 16 inches in ground to bedrock with 3 1/4 inch aluminum cap marked as shown:


Marked new bearing trees:

a 14" dbh Juniper bears North 27 1/2° East, 23.6 ft. scribed T13SR26ES35SCBT;
a 10" dbh Juniper bears North 62 1/2° West, 50.5 ft. scribed T13SR26ES34SCBT.

Nailed brass washer marked "LS 1026" in lower blaze. Raised a mound of stones 3 foot base to top of cap and buried the original stone south of cap. Set steel post with sign 54-4 6 feet north of and facing cap.

Painted 6 inch red band and faces red and nailed signs 54-3 and 54-4 on all bearing trees.

I hereby certify the above corner monument was re-established as herein described on JULY 28, 1982.



Magnetic Declination

19°15' EAST

REGISTERED PROFESSIONAL LAND SURVEYOR

David B. Armstrong

OREGON AUGUST 22, 1973 DAVID B. ARMSTRONG 1026

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 3 day of Sept, 1982
Robert D. Sargent by David B. Armstrong
(COUNTY OFFICIAL) (DEPUTY)