

# CERTIFIED RECORD OF LAND CORNER MONUMENTATION

## History of original corner establishment:

Original corner established by: W.H. Byars, Deputy Surveyor, under Contract No. 197, dated July 4, 1873.

Surveyor General Record States: Set volcanic stone 20x10x4 inches, for 1/4 section corner.

Survey 7G, by Vernon Glaze, dated June 18-July 30, 1914, Established 1/4 common corner Sec. 6-5. Set iron post brass cap marked and wooden post 4x4x4.0 scribed, set rock marked 1/4 CS erected monument of stone.



## Description of corner evidence found:

No Evidence of the original corner stone was found.

The iron post set by Glaze was found lying out of the ground. No evidence of the stone or wooden post was found.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

OREGON  
SEPT 19, 1995  
JACK L. WATSON  
2734

Renewal Date 6/30/2006

See Record Map of Survey No. 1745

## Description of monument and accessories set at corner location:

At the position determined by single proportion, I set a 5/8"x30" iron pin with 2" aluminum cap, 31 inches in the ground. The cap is stamped as shown in the diagram.

From which:

A 5/8"x30" iron pin bears N43°E, 64.15 feet, with attached red plastic cap marked CORNERSTONE SURVEYING INC.

A 5/8"x30" iron pin bears S43°W, 11.32 feet, with attached red plastic cap marked CORNERSTONE SURVEYING INC.

A 5/8"x30" iron pin bears S30°E, 21.01 feet, with attached red plastic cap marked CORNERSTONE SURVEYING INC.

A 5/8"x30" iron pin bears N30°W, 19.54 feet, with attached red plastic cap marked CORNERSTONE SURVEYING INC

I used a steel tape and magnetic compass, with 18° E. declination.

Date: November 29, 2005

Office of SURVEYOR County of GRANT  
State of OREGON, I hereby certify that the within instrument was filed in this office  
for record on the 2 day of DEC, 2005.  
Robert L. Basett by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)