


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T.13S., R.28E., INDEX L-18

History of original corner establishment:

This corner not previously established.



Description of corner evidence found:

Description of monument and accessories I establish to perpetuate the original location of this corner:

At position determined by survey (See Grant County Survey No.1746), set a 5/8" x 30" rebar pin with a 1" aluminum cap stamped as shown in the DIAGRAM, 20" in the ground, raised a 2' dia x 6" high mound of earth and stone From which:

A 6" Juniper bears N43°10'E, 3.9 ft. scribed X BT.
A 6" Juniper bears S34°50'W, 19.5 ft. scribed X BT.

Placed a brass washer stamped LS 49865 on blaze between X and BT.

DIAGRAM

T13S R28E
W 1/16
C-.-C
S 14
2005
PLS 49865

Measurements to accessories taken with a magnetic compass, declination 18° East, and distances measured with nylon clad steel tape.

I hereby certify that the above corner point was perpetuated as shown hereon on December 9, 2005

Witness: Bradley R. Cates, LSIT
David H. Herburger, Surv. Tech.

Office of County Surveyor County of Grant
State of Oregon . I hereby certify that the within instrument was filed in this office
for record on the 20 day of Dec, 2005

Robert D. Berger by _____
County Surveyor Deputy

