


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T.13S., R.28E., INDEX L-19

History of original corner establishment:

This corner not previously established.



Description of corner evidence found:

Description of monument and accessories I establish to perpetuate the original location of this corner:

At position determined by survey (See Grant County Survey No.1746), set a 2 1/2" x 30" aluminum pipe with a 3" aluminum cap stamped as shown in the DIAGRAM, 3" in the ground, raised a 5' dia x 2' high mound of earth and stone, From which:

A 4" Juniper bears N35°06'W, 63.5 ft. scribed X BT.

A 12" Juniper bears N26°45'E, 29.9 ft. scribed C 1/4 S 14 BT.

A 6" Juniper bears S78°36'E, 18.4 ft. scribed C 1/4 S 14 BT.

A 5/8"x 30" Rebar Pin bears S45°40'W, 17.5 ft. raised a 2 1/2' dia. X 1' high mound of stone around pin.

Placed a brass washer stamped LS 49865 on blaze above BT and a yellow plastic cap stamped FS&E on the pin.

DIAGRAM

T13S R28E
C 1/4

·
S 14
2005
PLS 49865

Measurements to accessories taken with a magnetic compass, declination 18° East, and distances measured with nylon clad steel tape.

I hereby certify that the above corner point was perpetuated as shown hereon on December 9, 2005

Witness: Bradley R. Cates, LSIT
David H. Herburger, Surv. Tech.

Office of County Surveyor _____ County of Grant
State of Oregon. I hereby certify that the within instrument was filed in this office
for record on the 28 day of Dec, 2005

Robert D. Boyett by _____
County Surveyor Deputy



RENEWAL DATE:
01/01/2006