


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T.13S., R.28E., INDEX M-19

History of original corner establishment:

This corner not previously established.



Description of corner evidence found:

Description of monument and accessories I establish to perpetuate the original location of this corner:

At position determined by survey (See Grant County Survey No.1746), set a 5/8" x 30" rebar pin with a 2" aluminum cap stamped as shown in the DIAGRAM, 12" below the ground surface, From which:

A 5/8"x 30" Rebar Pin bears S47°30'W, 16.3 ft.

A 5/8"x 30" Rebar Pin bears N39°08'W, 19.1 ft.

Placed a yellow plastic cap marked "FS&E on both pins.

DIAGRAM

T13S R28E
C
S1/16 . S14

C
2005
PLS 49865

Measurements to accessories taken with a magnetic compass, declination 18° East, and distances measured with nylon clad steel tape.

I hereby certify that the above corner point was perpetuated as shown hereon on December 7, 2005

Witness: Bradley R. Cates, LSIT
David H. Herburger, Surv. Tech.

Office of County Surveyor _____ County of Grant
State of Oregon _____. I hereby certify that the within instrument was filed in this office
for record on the 28 day of Dec, 2005

Robert D. Bayless
County Surveyor Deputy

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 13, 1999
KENNETH H. DELANO JR.
49865

RENEWAL DATE:
01/01/2006