


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

T.13S., R.29E., INDEX J-03

**History of original corner establishment:**

This corner was originally established by John B. David under G.L.O. contract number 131, dated June 8, 1869. Survey General notes state:

Set Stone 19x12x8 for 1/4 Sec. Corner.



**Description of corner evidence found:**

Found a 19"x12"x8" stone, marked 1/4, set in an old rock jack in an E-W fence line. Only four stones in this rockjack and the area is covered with stones. Accepted this as the best available evidence of the corner position.

**Description of monument and accessories I establish to perpetuate the original location of this corner:**

At the above described position (See Grant County Survey No. <sup>1711</sup>~~1710~~, set a 2-1/2" x 30" aluminum pipe monument w/3" dia. cap stamped as shown in the DIAGRAM, 18" in the ground in the rock jack, raised a 4' dia. x 1.5' high mound of stone and set the found stone north alongside the new monument, from which:

- A Juniper, 10" dia., bears N30°00'W, 50.1 ft., scribed "1/4 S7 BT"
- A Juniper, 14" dia., bears S15°30'E, 39.1 ft., scribed "1/4 S18 BT"
- A 5/8"x30" Rebar Pin bears N46°00'E, 18.6 ft.
- A 5/8"x30" Rebar Pin bears S50°30'E, 17.0 ft.
- Placed a yellow plastic cap marked "FSE SURVEY MARKER" on the pin.

**DIAGRAM**

T13S R29E  
S7  
1/4---  
S18  
2004  
PLS 49865

Measurements to accessories taken with a magnetic compass, declination 18° East, and distances measured with nylon clad steel tape.

I hereby certify that the above corner point was perpetuated as shown hereon on July 16, 2004

Witness: D. Mitchell Ferguson, LSIT  
David H. Herburger, Surv. Tech.

Office of County Surveyor \_\_\_\_\_ County of Grant  
State of Oregon \_\_\_\_\_. I hereby certify that the within instrument was filed in this office  
for record on the 2 day of Sept, 2004

Robert D. Buggs by \_\_\_\_\_  
County Surveyor Deputy



RENEWAL DATE:  
01/01/2006