


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T.13S., R.29E., INDEX L-01

History of original corner establishment:

This corner was originally established by John B. David under G.L.O. contract number 131, dated June 8, 1869. Survey General notes state:

Set Stone 14x10x7 1/4 Sec. Corner.



Description of corner evidence found:

No evidence of this corner is found. According to Tony Tirrico, resident, this corner was marked with a 2" brass cap that was set in an old fence. I believe this monument was set by Vernon Glaze. No record of this monument was found. The old fence has been replaced and a home constructed in this area. This corner was determined to be lost and is re-monumented at proportionate position.

Description of monument and accessories I establish to perpetuate the original location of this corner:

At proportionate measure (See Grant County Survey No. ^{1711 LDB} ~~1710~~), set a 2-1/2" x 30" aluminum pipe monument w/3" dia. cap stamped as shown in the DIAGRAM, 28" in the ground from which:

A 5/8"x30" Rebar Pin bears N38°30'W, 8.6 ft.

A 5/8"x30" Rebar Pin bears N70°00'W, 9.7 ft.

Place a yellow plastic cap marked "FSE SURVEY MARKER" ON both pins.

No references are set in the south quadrants due to the close proximity of a residence.

DIAGRAM

T13S
R28E R29E
1/4
S13 | S18
2004
PLS 49865

Measurements to accessories taken with a magnetic compass, declination 18° East, and distances measured with nylon clad steel tape.

I hereby certify that the above corner point was perpetuated as shown hereon on July 19, 2004

Witness: D. Mitchell Ferguson, LSIT
David H. Herburger, Surv. Tech.

Office of County Surveyor County of Grant
State of Oregon. I hereby certify that the within instrument was filed in this office
for record on the 2 day of Sept, 2004

Robert D. Baggett by _____
County Surveyor Deputy



RENEWAL DATE:
01/01/2006