


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T.13S., R.29E., INDEX S-9

History of original corner establishment:  
This corner not previously established.



Description of corner evidence found:

Description of monument and accessories I establish to perpetuate the original location of this corner:  
At position determined by survey(See Grant County Survey No. 1738), set a 2-1/2" x 30" aluminum pipe monument w/3" dia. cap stamped as shown in the DIAGRAM, 10" below ground surface, from which:  
  
A Juniper, 34" dia, bears West, 51.3 ft., scribed N1/16 S29 BT  
A Juniper, 8" dia., bears S48°E, 122.9 ft., scribed N1/16 S28 BT

DIAGRAM

T13S R29E  
N1/16  
S29 | S28  
2005  
PLS 49865

Measurements to accessories taken with a magnetic compass, declination 18° East, and distances measured with nylon clad steel tape.

I hereby certify that the above corner point was perpetuated as shown hereon on March 9, 2005

Witness: D. Mitchell Ferguson, LSIT  
David H. Herburger, Surv. Tech.



Office of County Surveyor County of Grant  
State of Oregon. I hereby certify that the within instrument was filed in this office for record on the 25 day of Nov, 2005

Robert A. Boyer by Deputy  
County Surveyor

RENEWAL DATE:  
01/01/2006