


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T.13S., R.29E., INDEX V-09

History of original corner establishment:

This corner was originally established by John B. David under G.L.O. contract number 131, dated June 8, 1869. Survey General notes state:

Set Stone 18x12x10 for Corner to Secs. 28, 29, 32 & 33



Description of corner evidence found:

Found an 18"x12"x10" stone, set upright, marked with 4 grooves on the south face. The east face has broken off.

Description of monument and accessories I establish to perpetuate the original location of this corner:

At the position of the found stone, set a 2-1/2" x 30" aluminum pipe monument w/3" dia. cap stamped as shown in the DIAGRAM, 14" in the ground, placed the stone north alongside the pipe and raised a 3' dia. x 1.5' high mound of earth and stone, from which:

- A 5/8"x30" Rebar Pin bears N46°W, 11.0 ft.
- A 5/8"x30" Rebar Pin bears N52°E, 10.5 ft.
- A 5/8"x30" Rebar Pin bears S45°E, 14.0 ft.
- A Juniper, 14" dia., bears S18°W, 56.4 ft., scribed T13S R29E S32 BT

Placed a yellow plastic cap marked "FS&E SURVEY MARKER" on all pins.

DIAGRAM

T13S R29E
S29 | S28

S32 | S33
2005
PLS 49865

Measurements to accessories taken with a magnetic compass, declination 18° East, and distances measured with nylon clad steel tape.

I hereby certify that the above corner point was perpetuated as shown hereon on March 1, 2005

Witness: D. Mitchell Ferguson, LSIT
David H. Herburger, Surv. Tech.

Office of County Surveyor _____ County of Grant
State of Oregon _____. I hereby certify that the within instrument was filed in this office
for record on the _____ day of _____, 2005

_____ by _____
County Surveyor Deputy

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 13, 1999
KENNETH H. DELANO JR.
49865

RENEWAL DATE:
01/01/2006