

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner established by: John B. David, Deputy Surveyor,
under Contract No. 131, dated June 8, 1869.

Surveyor General Record States: Set stone 16x12x8 inches,
for corner to Sections 10,11,14 and 15.

Description of corner evidence found:

No evidence of the original corner stone monument was found.



Renewal Date 6/30/2008

Description of monument and accessories set at corner location:

At the double proportionate corner position I set a 2½"x30" aluminum pipe with attached 3¼" aluminum cap, 24 inches in the ground, surrounded by a mound of stone. The cap is stamped as shown in the diagram.

From which:

A 5/8"x30" iron pin bears N55°E, 13.25 feet, with attached red plastic cap marked CORNERSTONE SURVEYING INC.

A 5/8"x30" iron pin bears S64°E, 10.22 feet, with attached red plastic cap marked CORNERSTONE SURVEYING INC.

A 5/8"x30" iron pin bears S42°W, 14.17 feet, with attached red plastic cap marked CORNERSTONE SURVEYING INC.

A 5/8"x30" iron pin bears N43°W, 9.59 feet, with attached red plastic cap marked CORNERSTONE SURVEYING INC.

I used a steel tape and magnetic compass, with 18° E. declination to tie references. See Grant County Survey No. 1811

Date: June 20, 2007

Office of County of
State of , I hereby certify that the within instrument was filed in this office
for record on the day of , 2007.
..... by
(COUNTY OFFICIAL) (DEPUTY)

J-17

**RECEIVED AND
FILED**

June 22, 2007
OFFICE OF COUNTY SURVEYOR
Attest: *[Signature]*