

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

U.S.F.S. INDEX No. P-2

History of original corner establishment:
This corner was not previously established

DIAGRAM

T13S R31E
W1/16

C--•--C

S19
1998
PLS 848

Description of Corner Evidence Found:
This corner was not previously established.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2-1/2"x30" aluminum pipe with 2-1/2"aluminum cap, stamped as Shown in DIAGRAM, 27" in the ground.

From which:

A Juniper 12" in dia., bears N12°27'E, 17.3 ft.,
scribed: C-W 1/16 S19 BT.
A juniper 16" in dia., bears S16°46'E, 14.8 ft.,
scribed: C-W 1/16 S19 BT.

Measurements to accessories taken with a Wild TCA 1100 total station.
Nailed a brass washer stamped PLS 848 above BT scribe as taken this survey. Nailed a Bearing Tree sign above the blaze and set a 2 1/4" aluminum chaining nail in base of tree.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1923
DOUGLAS M. FERGUSON
848

This work was performed by:
Douglas M. Ferguson, PLS 848
Witnessed by: D. Mitchell Ferguson
And Brad Cates
Date: 12-30-98

Office of SURVEYOR County of GRANT
State of OR I hereby certify that the within instrument was
filed in this office for record on the 17TH day of JUNE, 1999
Robert A. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)

Refer to Grant County Partition Plat No. 99-15