


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

U.S.F.S. INDEX No. P-3

History of original corner establishment:

This corner was not previously established

DIAGRAM



Description of Corner Evidence Found:

This corner was not previously established



Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2-1/2"x30" aluminum pipe with 2-1/2"aluminum cap, stamped as Shown in DIAGRAM, 28" in the ground.

From which:

- A Juniper 27" in dia., bears N54°53'W, 75.2ft., scribed: C1/4 S19 BT.
- A Juniper 12" in dia., bears N00°40'W, 35.6ft., scribed: C1/4 S19 BT.
- A Juniper 8" in dia., bears S48°31'E, 47.4ft., scribed: C1/4 S19 BT.
- A Juniper 12" in dia., bears S80°00'W, 32.4ft., scribed: C1/4 S19 BT.

Measurements to accessories taken with a Wild TCA 1100 total station. Nailed a brass washer stamped PLS 848 above BT scribe as taken this Survey. Nailed a Bearing Tree sign above the blaze and set a 2-1/4" Aluminum chaining nail in base of tree.



This work was performed by:
Douglas M. Ferguson, PLS 848
Witnessed by: D. Mitchell Ferguson
And Brad Cates
Date: 12-30-98

Office of SURVEYOR County of GRANT
State of OR I hereby certify that the within instrument was
filed in this office for record on the 17th day of JUNE, 1999
Robert D. Begett by _____
(COUNTY OFFICIAL) (DEPUTY)

Refer to Grant County Partition Plat No. 79-15