


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

T.13S., R.34E., INDEX C-1

**History of original corner establishment:**

This corner was originally established by John B. David under G.L.O. contract No. 131, dated June 8, 1869. Survey General notes state:

Set stone 16x10x8 for 1/4 sec. corner.



**Description of corner evidence found:**

No evidence of this corner is found. Set monument at proportionate measure.

**Description of monument and accessories I establish to perpetuate the original location of this corner:**

At proportionate position determined by survey, Land Partition Plat 2007-\_\_\_\_\_, Set a 2-1/2" x 30" aluminum pipe monument w/3" dia. cap stamped as shown in the DIAGRAM, 18" in the ground, raised a 1' high x 3' dia. mound of earth and stone, from which:

- A 5/8" iron pin w/yellow plastic cap bears N60°36'W, 10.06 ft.
- A 5/8" iron pin w/yellow plastic cap bears N56°42'E, 10.56 ft.
- A 5/8" iron pin w/yellow plastic cap bears S57°59'E, 10.16 ft.
- A 5/8" iron pin w/yellow plastic cap bears S53°55'W, 10.61 ft.

**DIAGRAM**

T13S  
R33E R34E  
1/4  
S1 | S6  
2007  
PLS 49865

Yellow plastic caps on 5/8" pins are marked "FSE"

Measurements to accessories taken with Topcon Hyper-Lite GPS.

I hereby certify that the above corner point was perpetuated as shown hereon on November 13, 2007

Witness: D. Mitchell Ferguson, LSIT  
David H. Herburger, Surv. Tech.



Office of County Surveyor County of Grant  
State of Oregon. I hereby certify that the within instrument was filed in this office  
for record on the 5<sup>th</sup> day of NOVEMBER, 2007-2010

M. J. Sp... by \_\_\_\_\_  
County Surveyor Deputy

See Grant County Land Partition Plat 2007- 28