

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:


Corner established by Bamford Robb under General Land Office Contract No. 383 dated March 26, 1881.

Surveyor General's records state:

Set a basalt stone 18"x14"x10" in mound of stone for cor. to sec's 16,17,20,21.

From which:

a pine, 10" dia., bears N.14°W., 25 lks.
a pine, 14" dia., bears N.61°E., 24 lks.



Description of corner evidence found:

At the assumed corner location found a large stone mound measuring 3 feet base and 2 1/2 feet high on edge of a sharp rock outcrop on a steep west slope hillside. The original stone was not found or identified although records indicate that R.G.K. (Robert G. Keller U.S.F.S.) found a basalt stone 24"x8"x8" 12" above ground marked with 4 notches on East and 3 notches on South faces in June 1962. R.G.K. also states he posted form 458 tag on NW BT. Found the original NW bearing tree, a Ponderosa Pine, 17" D.B.H., bears North 2° West, 15.5 feet to face, marked with a chopped open blaze face with visible scribing "13 R35" and a form 458 tag marked "cor. 25 lks. S4°E". initialed "GWD, RGK 6/62". Found possible root hole of NE bearing tree, bears N.42°E., 19 feet to center. A basalt stone 18"x14"x10" was found in the stone mound with no identifiable marks.

Description of monument and accessories | established to perpetuate the original location of this corner:


As evidence in vicinity of corner agrees with G.L.O. original record, at the location of the center of the original mound of stone of stone set a 30" long 2 1/2" O.D. aluminum pipe on bedrock surface with 3 1/4" aluminum cap marked:

Marked new bearing trees:

A Douglas Fir, 12" DBH, bears North 47° East, 35.4 feet, scribed "T13S R35E S16 BT";
a Juniper, 11" DBH, bears South 12° East, 47.8 feet, scribed "T13S R35E S21 BT";
a Douglas Fir, 14" DBH, bears South 80° West, 10.2 feet, scribed "T13S R35E S20 BT".

From which original bearing tree:

A Ponderosa Pine, 17" DBH, bears North 2° West, 15.6 feet to center, marked with visible scribing "13 R35" on chopped open blaze face.



Declin. 14°E

Raised a large mound of stone fully supporting aluminum pipe measuring 3 feet base to top of cap. Painted 6" red band and faces red and nailed signs 54-3 and 54-4 on bearing trees. Nailed brass washers stamped "LS 1026" on new bearing trees. Set steel posts north and east of pipe with signs 54-2 and 54-4.

I hereby certify the above corner monument was re-established as herein described on August 27, 1981.

Witnesses: William S. DeGroot LS 1633 Shelby H. Griggs Chairman

Office of Surveyor County of Grant
State of Oregon I hereby certify that the within instrument was filed in this office
for record on the 19 day of Oct, 1981
Robert D. Begett by _____
(COUNTY OFFICIAL) (DEPUTY)

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

David B. Armstrong
7/29/81 OREGON
AUGUST 22, 1973
DAVID B. ARMSTRONG
1026

Form R6-7100-57 (9/71)