

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner # R-6

DIAGRAM

T13S R35E

W $\frac{1}{16}$ $\frac{520}{529}$

Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2 1/2" x 30" Aluminum Pipe with 3" Aluminum Cap
rising 6" in stone mound.

Cap marked

As witnesses:

A 9" Ponderosa Pine Brs. S28°W 8.4'
marked W 1/16 S29 BT.

A 10" Ponderosa Pine Brs. N72°W 7.4'
marked W 1/16 S20 BT.

W $\frac{1}{16}$ $\frac{520}{529}$
1986
LS1020

I hereby certify the above corner point was
established as described in June, 1986. U.S.F.S.
bearing tree signs were placed on all BTs and
a 6" red band was painted around each BT.

Office of Surveyor..... County of Grant.....

State of Oregon....., I hereby certify that the within instrument was filed in this office

for record on the 3 day of Sept, 1986

Robert D. Gault by

(COUNTY OFFICIAL)

(DEPUTY)

REGISTERED
PROFESSIONAL
LAND SURVEYOR

ORIGON
FEBRUARY 14, 1975
GEORGE W. COLVIN, JR.
1990