


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner established in 1881
by Robb & Graden.
Set basalt stone 15x10x8 in mound of
stone from which:
A 10" Pine Brs. S72°W 11 lks. (7.3')

Corner # R-7



Description of corner evidence found:

Found 18"x10"x8" stone rising 6" in well
preserved stone mound. (No markings on stone)
Stone mound was man made and ancient in an
undisturbed area and I accepted this position as
corner location.
No evidence of original bearing tree remains.

Description of monument and accessories I established to perpetuate the
original location of this corner:

Set 2 1/2"x30" Aluminum pipe with 3" aluminum cap
rising 9" in stone mound. Buried original stone at
bottom of mound.

Cap marked

As witnesses:

A 11" Fir Brs. S40°E 9.1'
marked 1/4 S29 BT
A 13" Fir Brs. N70°E 28.8'
marked 1/4 S20 BT

T135 R35E

$\frac{1}{4}$ S 20
—
S 29
1986
LS1020

I hereby certify the above corner point was
perpetuated as described in June, 1986. U.S.F.S.
bearing tree signs were placed on all BTs and
a 6" red band was painted around each BT.

Office of Surveyor County of Grant
State of OREGON, I hereby certify that the within instrument was filed in this office
for record on the 3 day of Sept, 1986
Robert D. Begett by _____
(COUNTY OFFICIAL) (DEPUTY)

