

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. Line Tree 224' West From V-3

History of original corner establishment:

Line Tree was originally established by
Bamford Robb, in March 1881, under
General Land Office Contract No. 383.
The U.S. Surveyor Generals Notes State:
36.42 Ch. Pine 26" dia.
39.82 Ch. (1/4 cor.)

DIAGRAM
T13S R35E
LINE TREE
S30
-.-
S31
1987
RLS 848

Description of corner evidence found:

Found root hole and a 28" pine windfall with 2
blazes on what would be the west face, and the
East face rotted away, lying alongside the said
root hole. Accepted the root hole as LINE TREE locus.

**Description of monument and accessories I established to perpetuate the
original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET 24" in the ground, in the root hole of the original
LINE TREE.

From Which:

A Pine 10" dia., Bears S41°W., 7.0 ft., scribed: LINE TREE S31 BT

A Pine 10" dia., Bears N43°W., 8.9 ft., scribed: LINE TREE S30 BT

Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.

Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence post with
warning & Boundary Signs, West 3 ft. from the new monument.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1969
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: Sept. 2, 1987
Refer to Map of Survey No. 1013

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*7*..... day of.....*May*....., 19.....*88*.....
.....*Robert D. Bayne*..... by.....
(COUNTY OFFICIAL) (DEPUTY)