

# CERTIFIED RECORD OF LAND CORNER MONUMENTATION

## History of original corner establishment:

*Original corner established in 1881  
by Robb & Graden.  
Set basalt stone 22x16x9 in mound  
of stone.*

*Corner # V-7*

### DIAGRAM

*T135 R35E*

|               |                 |
|---------------|-----------------|
| $\frac{1}{4}$ | S 29            |
| 4             | $\frac{532}{-}$ |
|               | 532             |

## Description of corner evidence found:

*Found deteriorating stone mound on steep, south  
facing side hill. 24"x16"x9" unmarked stone 30'  
downhill. Held center of mound as corner  
position.*

## Description of monument and accessories | established to perpetuate the original location of this corner:

*Set 2 1/2" x 30" aluminum pipe with 3" aluminum cap  
rising 4" in stone mound.*

*Cap marked*

### New BTs:

*A 17" Fir brs. N20°E 13.0'*

*marked 1/4 S29 BT.*

*A 14" Fir brs. S57°W 29.2'*

*marked 1/4 S32 BT.*

*T135 R35E*

|               |                 |
|---------------|-----------------|
| $\frac{1}{4}$ | S 29            |
| 4             | $\frac{532}{-}$ |
|               | 532             |
|               | 1986            |
|               | LS1020          |

*I hereby certify the above corner point was  
perpetuated as described in June, 1986, U.S.F.S.  
bearing tree signs were placed on all BTs and  
a 6" red band was painted around each BT.*

Office of Surveyor County of Grant

State of OREGON, I hereby certify that the within instrument was filed in this office

for record on the 3 day of Sept, 1986

Robert D. Bryant by \_\_\_\_\_

(COUNTY OFFICIAL)

(DEPUTY)

