

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


Corner # 2-5

History of original corner establishment:

Original corner established in 1881 by Robb & Graden.
Set basalt stone 20x10x8 in mound of stone.

Retracement in 1901 by G. Campbell!
Found 20x10x8 stone in mound of stone from which:

A 8" Black Pine brs. N 45° E 14 lrs. (9.2')
A 18" Tamarack brs. N 60° E 50 lrs. (33.0')
(bearing in GLO notes recorded in wrong quadrant)



Description of corner evidence found:

Found 24"x14"x10" stone, marked + on top, 5 notches East and 1 notch West, in stone mound.

A dead & down Tamarack Northwest with scribes; root position undeterminable.

A 7" Lodgepole Pine brs. N 42° E 8.5' scribes visible.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2 1/2" x 30" aluminum pipe with 3" aluminum cap rising 14" in stone mound. Buried original stone in, downhill, bottom of mound.

Cap marked
SC

New BTs:

A 7" Lodgepole Pine brs. N 58° W 12.5' marked T135 R35E S 31 SC BT.

T135 R35E

531 1532
-1-

1986
LS1020

I hereby certify the above corner point was perpetuated as described in June, 1986. U.S.F.S. bearing tree signs were placed on all BTs and a 6" red band was painted around each BT.

Office of SURVEYOR County of GRANT
State of OREGON, I hereby certify that the within instrument was filed in this office for record on the 3 day of Sept, 1986
Robert D. Regatt by _____
(COUNTY OFFICIAL) (DEPUTY)

