


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Corner #2-9

History of original corner establishment:

*Original corner established in 1881
by Robb & Graddon:
Set basalt stone 20x14x12 in mound
of stone from which:
A 25" Pine brs. N 73° W 19 lks. (12.5')
Retracement in 1901 by G. Campbell:
Found basalt stone marked as described
from which:
A 30" Yellow Pine brs. N 58° E 63 lks. (41.5')
A 25" Pine brs. N 73° W 19 lks. (12.5')*



Description of corner evidence found:

*Found 22"x16"x12" stone, 4 notches East and 2
notches West, in center of stone mound.*

*Large dead and down Pine, scribes visible, root hole
brs. N 77° W 13.4'.
A 18" Ponderosa Pine brs. N 54° E 41.5', scribes
visible.*

Description of monument and accessories I established to perpetuate the
original location of this corner:

*Set 2 1/2" x 30" aluminum pipe with 3" aluminum cap
rising 6" in stone mound. Buried original stone
along side.*

*Cap marked
SC*

*New BT:
A 8" Ponderosa Pine brs. N 77° W 4.4'
marked T135 R35E 532 SC BT.*

*T135 R35E
532 533*

!-

*1986
LS1020*

*I hereby certify the above corner point was
perpetuated as described in June, 1986, U.S.F.S.
bearing tree signs were placed on all BTs and
a 6" red band was painted around each BT.*

Office of.....*SURVEYOR*..... County of.....*GRANT*.....
State of.....*OREGON*....., I hereby certify that the within instrument was filed in this office
for record on the.....*3*..... day of.....*Sept*....., 19*86*
.....*Robert D. Smith*..... by.....
(COUNTY OFFICIAL) (DEPUTY)

