CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. C-24

History of original corner establishment:

Corner was originally established in 1893, by Chas. G. Caspary, Grant County Surveyor. This corner was established as the NW Corner of the Townplat of Dayville. Caspary's Map does not show what was set at this corner. In 1910 Micheal Spears, Grant County Surveyor found this corner and states that it is a rock marked 1/16. Spears states he reset 2' above ground, deposit of glass under under cover with earth 4' over glass then put in the rock. (This is not clear to me, I can't make out his writing)
See the HISTORY & NARRATIVE for more detail as to the original establishment of this corner.

DIAGRAM

T13S R26E
E1/16
C-.-C
S 1
1988
PLS 848

Description of corner evidence found:

No trace of any original evidence is identified,this area has been developed extensively since 1910.
Corner is established as described in the HISTORY & NARRATIVE of this referenced Map of Survey No. 1050.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" Aluminum Pipe with 3-1/2" Aluminum Cap Stamped as shown in the DIAGRAM set 26" in the ground.
From Which:
Set 5/8"x30" iron pins with plastic caps marked PLS 848 as follows:
South 10.0 ft. and East 10.0 ft.
Measurements to pins taken with metal tape and magnetic compass with 20° East Declination set off.
Power pole N36°W., 2.0 ft.
Edge Pavement West 12.0 ft.

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt.Vernon Oregon.
On: Sept. 7, 1988
Refer to Map of Survey No. 1050
Witnesses: D.Mitchell Ferguson & Ken Delano

Office of.....Surveyor.....*County of*.....Grant.....
State of.....Oregon....., *I hereby certify that the within instrument was filed in this office for record on the*...27...*day of*.....Sept....., *19*..88
.....Robert D. Bagent..... *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

C-24