CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. C-25

History of original corner establishment:

Corner was originally established by W. Byars, in 1873, under General Land Office Contract No. 185. U.S. Surveyor Generals Notes State: Set 1/4 Sec. Cor, A Stone 18x8x6.

In 1969 R.D. Bagett found a basalt stone marked "1/4" and a 1" iron pipe at this position. See Map of Survey No 148, of the Grant County Survey Records.

DIAGRAM

T13S
R26E R27E
1/4
S1!S6
1988
PLS 848

Description of corner evidence found:

No trace of the original evidence is found.
No trace of evidence as described by Bagett in 1969 is found.
Established Corner as based on said Map of Survey No. 148, at the position as shown on that map. See this Map of Survey No. 1050 for details.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" Galvanized Iron Pipe with 2-/12 Brass Cap Stamped as shown in the DIAGRAM set 26" in the ground.
From Which:
Set 5/8"x30" iron pins with plastic caps marked PLS 848 as follows:
East, 10.0 ft. and West 10.0 ft;
Measurements to pins taken with metal tape and magnetic compass with 20° East Declination set off.
Corner falls in a N-S Fence, in the West edge of hay field.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS N. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt.Vernon Oregon.
On: June 14, 1988
Refer to Map of Survey No. 1050
Witnesses: D.Mitchell Ferguson & Ken Delano

Office of Surveyor *County of* Grant
State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 27 *day of* Sept, 19 88
Calvert D. Bagett *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

C-25