CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. E-23

History of original corner establishment:

Corner was originally established by J. Owen, in 1873, under General Land Office Contract No. 194.
U.S. Surveyor Generals Notes State:
Set Stone 20x15x6 for 1/4 Sec. Cor.

DIAGRAM

T13S R26E
S1
1/4-.-
S12
1988
PLS 848

Description of corner evidence found:

Examined all the stones of near call size, in and around the fence corner and search area. No trace of evidence is identified. Established corner position at proportionate measure between the Section Corners found 1/2 mi. East and West.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" Aluminum Pipe with 3-1/2" Aluminum Cap Stamped as shown in the DIAGRAM set 10" in the ground and raised a mound of stone and earth around the pipe.
From Which:
Set 5/8"x30" iron pins with plastic caps marked PLS 848 as follows:
North 10.0 ft. and South 10.0 ft.
Measurements to pins taken with metal tape and magnetic compass with 20° East Declination set off.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt.Vernon Oregon.
On: July 1988
Refer to Map of Survey No. 1050
Witnesses: D.Mitchell Ferguson & Ken Delano

Office of Surveyor *County of* Grant
State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 21 *day of* Sept, *19* 88
Courtd Rayt *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

E-23