# CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. E-24

**History of original corner establishment:**

Grant County Survey Records show no previous establishment of this Cor.

There is a 5/8" iron pin set as a boundary agreement corner, N89°04'49"W., 11.79 from this corner. Such pin is shown on Map of Survey No. 226, of the Grant County Survey Records and should stand on its own as a boundary agreement corner, independent of this 1/16 corner.

**DIAGRAM**

T13S R26E
S 1
E1/16-.-
S12
1988
PLS 848

**Description of corner evidence found:**

Grant County Survey Records show no previous establishment of this Cor.
See this referenced Map of Survey No. 1050 for method of establishment.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

Set 2-1/2"x30" Aluminum Pipe with 3-1/2" Aluminum Cap Stamped as shown in the DIAGRAM set 25" in the ground.
From Which:
Set 5/8"x30" iron pins with plastic caps marked PLS 848 as follows:
North 10.0 ft. and South 10.0 ft.
Measurements to pins taken with metal tape and magnetic compass with 20° East Declination set off.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt.Vernon Oregon.
On: July 1988
Refer to Map of Survey No. 1050
Witnesses: D.Mitchell Ferguson & Ken Delano

*Office of* Surveyor *County of* Grant
*State of* Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 27 *day of* Sept, *19* 88
Robert D. Leggett *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

E-24